

Andrew RAYNER
Serial No. 10/571,062
May 11, 2010

AMENDMENTS TO THE CLAIMS:

The following listing of claims supersedes all prior versions and listings of claims in this application:

1. (Currently Amended) A method of determining whether one or more of at least two signal paths has been altered, the paths each having a transit time associated therewith, the method comprising ~~the steps of:~~

monitoring the difference between the transit time of a first signal path and the transit time of a second signal path such that a change in the difference between the transit times of the two paths is detected; [[and,]]

comparing the detected change in difference against a threshold value; and
in dependence at least in part on any such detected change exceeding the threshold value, generating an alarm signal.

2. (Original) A method as claimed in claim 1, wherein the difference between the transit times of the paths is monitored by: introducing marker signals onto the first and second paths at respective entry points; receiving the marker signals at respective collection points along the first and second paths; and, monitoring the arrival times of the marker signals in one path relative to the arrival times of marker signals in the other path.

Andrew RAYNER
Serial No. 10/571,062
May 11, 2010

3. (Original) A method as claimed in claim 2, wherein for each marker signal introduced onto one path, a corresponding marker signal is introduced onto the other path, and wherein the difference in the arrival times of corresponding marked signal is used to monitor the difference in the respective transit times associated with the first and second paths.

4. (Original) A method as claimed in claim 3, wherein the difference in the time of arrival of marker signals is monitored.

5. (Previously Presented) A method as claimed in claim 2, including the step of introducing into each marker signal an indication of the relative time at which that marker signal was introduced onto a path, the relative time being measured relative to a clock source.

6. (Currently Amended) A method as claimed in claim 2, wherein a marker signal in one ~~stream~~ path includes an indication of the time at which that marker signal was introduced relative to the time at which a marker was introduced into the other path ~~stream~~.

Andrew RAYNER
Serial No. 10/571,062
May 11, 2010

7. (Previously Presented) A method as claimed in claim 1, wherein the first and second paths extend between a common upstream location and a common downstream location.

8. (Currently Amended) A method as claimed in claim 6, wherein the first and second paths extend between a common upstream location and a common downstream location and wherein the common upstream clock source is provided located at the upstream location.

9. (Previously Presented) A method as claimed in claim 1, wherein each path carries a respective signal stream, the signal stream carried by the first path being representative of the same content as the signal carried by the second path.

10. (Previously Presented) A method as claimed in claim 7, wherein the relative time of arrival of marker signals is measured relative to a common downstream clock source located at the downstream location.

11. (Original) A method as claimed in claim 1, wherein the difference between the transit times of the two paths is determined by receiving marker signals from

Andrew RAYNER
Serial No. 10/571,062
May 11, 2010

respective entry points on the first and second paths, and monitoring the arrival times of the marker signals.

12. (Original) A method as claimed in claim 11, wherein each marker signal includes a time stamp indicative of the time at which that marker signal was introduced onto a path relative to a clock source, the method including the further step of reading the time stamps and taking into account the time difference between the time at which packets have been introduced onto the first and second paths when determining the difference in the transit times of the two paths.

13. (Previously Presented) A method as claimed in claim 1, wherein each path carries video data.

14. (Currently Amended) A receiving station for receiving data from a sending station sent over at least a first path and a second path, the paths each carrying respective marker signals, the receiving station ~~having~~ comprising:

a reading stage for detecting the presence of marker signals, and for monitoring the time of arrival of marker signals from one path relative to the time of arrival of marker signals from the other path, and

Andrew RAYNER
Serial No. 10/571,062
May 11, 2010

a processing stage for determining, in dependence at least in part on the monitored arrival times, the difference in transit times between marker signals travelling along the first path and the transit time of marker signals travelling along the second path, an alarm signal being generated if a change in the difference between the transit times along the first and second paths exceeds a threshold value.

15. (Currently Amended) A receiving station as claimed in claim 14, wherein the processing stage is configured to perform the following steps:

(i) calculate the difference between the transit time of a marker on one path and the transit time of another marker on the other path;

(ii) repeat step (i) for each pair of subsequently received markers; and[[,]]

(iii) if a change in the difference in transit time associated with received pairs of markers reaches [[a]] the threshold value, generate [[an]] the alarm signal.

16. (Original) A receiving station as claimed in claim 15, wherein an alarm signal is generated only if the threshold value has been reached a predetermined number of times within a time period.

17. (Previously Presented) A receiving station as claimed in claim 14, the receiving and sending stations being connectable to the network, the sending station

Andrew RAYNER
Serial No. 10/571,062
May 11, 2010

being configured, when connected to the network to: send data on a plurality of paths, the data including marker signals, each marker signal including a respective time stamp, the time stamp of a marker signal being indicative of the relative time at which that marker signal was transmitted.

18. (Previously Presented) A receiving station as claimed in claim 17, wherein the sending station includes a common clock source, the indication of a relative time included in each stamp being a time measured relative to the common clock source.

19. (Previously Presented) A receiving station as claimed in claim 17 wherein the sending station and the receiving station are separated by a distance of more than 10 km.

20. (Previously Presented) A receiving station as claimed in claim 19, wherein the distance separating the sending station and the receiving station is at least 100 km.

Andrew RAYNER
Serial No. 10/571,062
May 11, 2010

21. (Currently Amended) A receiving station which is connectable to a plurality of paths, each path having a transit time associated therewith for data transport along that path, the receiving station ~~having~~ comprising:

means for~~[[:]]~~ monitoring the difference between the transit time of a first path and the transit time of a second path such that a change in the difference between the transit times of the two paths is detected; ~~[[and,]]~~

means for comparing the detected change in difference against a threshold value; and

in dependence at least in part on any such detected change exceeding the threshold value, means for generating an alarm signal.